

Бор алмазный СИСТЕМА конусный усеченный

ИМ-7.5560/2306

алмазный, FG (турбинный), конусный усеченный,
форма ISO 168 / 170 / 171 / 172 / 173 / 197 / 199

Система НП ООО, Беларусь



Характеристики

Тип бора	алмазный
Хвостовик	FG (турбинный)
Форма	конусный усеченный
Форма по ISO	168 / 170 / 171 / 172 / 173 / 197 / 199

Описание

Форма ISO 173

Диаметр, мм	1.0	1.2	1.4	1.6	1.8	2.1	2.3
19 мм – стандартный							
	806.314.173.504.	010	012	014	016		021
	806.314.173.514.	010	012	014	016		021
	806.314.173.524.		012	014	016	018	023
	806.314.173.534.		012	014	016	018	023
	806.314.173.544.			014	016	018	021 023
21 мм – удлиненный							
	806.315.173.514.					021	
	806.315.173.524.						023
	806.315.173.534.						023

Форма ISO 168 / 170 / 171 / 172 / 197 / 199

???????, ??		1.0	1.2	1.4	1.6	1.8
19 ??, ????? ISO 168						
	806.314.168.524.		012			
19 ??, ????? ISO 170						
	806.314.170.514.	010	012			
	806.314.170.524.		012	014		
	806.314.170.534.		012	014		
19 ??, ????? ISO 171						
	806.314.171.514.	010	012	014		
	806.314.171.524.		012	014	016	
	806.314.171.534.		012	014	016	
19 ??, ????? ISO 172						
	806.314.172.504.	010	012	014	016	
	806.314.172.514.	010	012	014	016	
	806.314.172.524.		012	014	016	018
	806.314.172.534.		012	014	016	018
	806.314.172.544.			014	016	018
19 ??, ????? ISO 197						
	806.314.197.524.		012			
19 ??, ????? ISO 199						
	806.314.199.534.			014		